



**LinTech**  
Linking the world

LinTech  
Factory: ZI Tit Mellil, Lot 2 N°4, Tit Mellil, Casablanca  
Headquarters: N°46, Avenue El Walâa & Rue Abdelkhalek  
Torres -Dakhla -Oued Eddahab  
+212 5 22 22 41 03  
[commercial@litech.ma](mailto:commercial@litech.ma)  
[www.litech.ma](http://www.litech.ma)

## Non-PoE, Unmanaged switch: LN-NM-8P

### Product Description

LN-NM-8P is a full Gigabit Division-type Ethernet switch developed independently, which provides 8 10/100 / 1000M adaptive RJ45 ports. Each RJ45 port supports MDI / MDIX automatic flipping and linear speed forwarding.

Can quickly adapt to a variety of complex environments. The device is plug-and-play, no configuration, easy to use. It can be used for security surveillance, hotel, campus, factory dormitory access layer, and wireless coverage of small and medium-sized enterprises.

### Product model and appearance

LN-NM-8P	<ul style="list-style-type: none"><li>● 8*10/100/1000M RJ45 ports</li><li>● Backplane Bandwidth: 16Gbps</li><li>● Packet Forwarding Rate:11.9Mpps</li><li>● Port supports MDI / MDIX automatic flip function</li></ul>
----------	--

### Product performance

- Large buffer design, high-definition video does not freeze.
- Support IEEE 802.3x full-duplex flow control and Backpressure half-duplex flow.
- Each RJ45 port supports MDI/MDIX auto flip and wire-speed forwarding function

### Product reliability

- The host has a low power consumption design and natural heat dissipation to ensure stable operation of the product.

- 0~45°C working temperature improves product stability in a wide temperature environment.

### Easy to use

- Plug and play, no need to configure, simple and convenient.
- Users can use the power indicator (Power), port status indicator (Link/Act).

### Physical Characteristics

Model	LN-NM-8P
Downlink ports	8*10/100 /1000M RJ45 ports
Bandwidth	16Gbps
Packet Forwarding Rate	11.9Mpps
MAC address	4K
LED Indicator	Link / Act, Power
Transmission mode	IEEE802.3 full duplex flow control and backpressure half duplex flow control
Standard Protocol	IEEE802.3i 10 BASE-TX IEEE802.3u 100 BASE-TX IEEE802.3ab 1000 BASE-T IEEE802.3x Flow Control IEEE802.3az EEE
Size	139mm × 66mm ×26mm
Power supply	AC 100~240V 50/60HZ
Working temperature	Working Temperature: 0°C~45°C, Humidity: 10% ~ 90% Storage Temperature : - 20°C~ 70°C, Humidity : 5% ~ 95%

### Ordering information

LN-NM-8P	8*10/100/1000M RJ45 Ports
----------	---------------------------

**« 1 year warranty »**